BEST AVAILABLE COPY

PATENT ABSTRACTS OF JAPAN

(11)Publication number:

05-205342

(43)Date of publication of application: 13.08.1993

(51)Int.CI.

G11B 11/10 G11B 7/00 G11B 7/125

(21)Application number: 04-224065

(71)Applicant: INTERNATL BUSINESS MACH

CORP (IBM>

(22)Date of filing:

24.08.1992

(72)Inventor: CALL DAVID E

TIPTON LAWRENCE D

(30)Priority

Priority number: 91 779440

Priority date: 18.10.1991


Priority country: US

(54) METHOD FOR CALIBRATING WRITING SIGNAL POWER LEVEL AND MOBILE MEDIUM MEMORY DEVICE

(57)Abstract:

PURPOSE: To obtain an optimum reading signal by supplying plural writing signal power levels to a marking source, correlating the measurement value of the amplitude of a reading signal to the specified signal power level and deciding the calibrated writing signal power

CONSTITUTION: A track in a magneto-optical medium 30 is selected for a calibration test, under the control of a microprocessor 40. The sectors 00-23 of the selected track are erased. The entire writing signal power levels of the laser 67 are expressed as an integer value and converted from digital into the analog. A sector number is set to n=00, and also the writing signal power level is selected. Test patterns are respectively marked by the successively increased writing signal power level from an offset writing signal power level W0, the test pattern is read and the reading signal is correlated with the writing signal power level. The adjustment portion of the writing signal power level from an offset is calculated through the



use of min. square parameter, and the writing signal power level is determined.

LEGAL STATUS

[Date of request for examination]

24.08.1992

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or